



**BOSCH**  
Invented for life

## DS7447V2 Series LCD Keypads



- ▶ Adjustable volume, display brightness, and display contrast
- ▶ Accessible instruction label
- ▶ Programmable emergency keys

The DS7447V2 is a four-wire alphanumeric liquid crystal display (LCD) keypad that works with the DS7060, DS7080iP-32, DS7200 Series, and DS7400Xi Series Control Panels. It supports all system functions. The keypad is required for programming the control panel locally.

### Functions

#### Adjustable Volume and Display

Adjust the non-alarm volume, display brightness, and display contrast at the keypad.

#### Accessible Instruction Label

Basic user instructions are on a pull-out slide that you can install to pull from either the left or the right.

#### Programmable Emergency Keys

The three unmarked keys across the bottom row of the keypad are programmable as a fire emergency key, a special emergency key, and a panic key. Adhesive labels are provided.

### Certifications and Approvals

Region	Certification	
Europe	CE	1999/5/EC Radio Equipment and Telecommunications Equipment (R&TTE), 2004/108/EC EMC Directive (EMC), 2006/95/EC Low-Voltage Directive (LVD)
Belgium	INCERT	B-509-0004/c
All DS7447V2 Keypad Models:		EN50131-1 Grades 1, 2, and 3
DS7447V2-FRA Keypad:		NF A2P Type 2 Certification number: 122000076-01

### Installation/Configuration Notes

#### Compatibility Information

Control Panels	DS7060, DS7080iP-32, DS7400Xi Series, DS7200 Series
----------------	---

#### Wiring and Mounting Considerations

The wire length between the keypad and the control panel cannot exceed 305 m (1000 ft). Do not mount the keypad outdoors.

Number of Keypads	Wire Type	Keypad Distance from Control Panel
Up to two	Unshielded, four-wire, 0.8 mm (22 AWG)	Up to 305 m (1000 ft)
Up to three	Unshielded, four-wire, 1.2 mm (18 AWG)	Up to 305 m (1000 ft)

### Parts Included

Quant.	Component
1	Keypad assembly
1	Info card slide
2	Info cards
1	Ferrite bead with installation instructions
1	Literature – Installation manual

### Technical Specifications

#### Environmental Considerations

Relative Humidity:	5% to 93% at +32°C (+90°F), non-condensing
--------------------	--

Temperature (Operating):	0°C to +50°C (+32°F to +122°F)
--------------------------	--------------------------------

#### Power Requirements

Current Draw:	95 mA idle; 200 mA max (with speaker volume and backlight brightness on)
---------------	--

Voltage (Operating):	12 VDC
----------------------	--------

#### Product Characteristics

Dimensions:	12 cm x 21 cm x 2 cm (4.6 in. x 8.2 in. x 0.8 in.)
-------------	---

Weight:	439 g (15.5 oz)
---------	-----------------

### Ordering Information

#### DS7447V2-EXP LCD Keypad

**DS7447V2-EXP**

For export. Provides volume controls, display brightness controls, display contrast controls, and three programmable emergency keys.

#### DS7447V2-HU LCD Keypad

**DS7447V2-HU**

For use in Hungary. Provides volume controls, display brightness controls, display contrast controls, and three programmable emergency keys.

#### DS7447V2-BEL LCD Keypad

**DS7447V2-BEL**

For use in Belgium. For export. Provides volume controls, display brightness controls, display contrast controls, and three programmable emergency keys.

#### DS7447V2-FRA LCD Keypad

**DS7447V2-FRA**

For use in France. Provides volume controls, display brightness controls, display contrast controls, and three programmable emergency keys. NF A2P Type 2 Certification number: 122000076-01.

#### DS7447V2-NL LCD Keypad

**DS7447V2-NL**

For use in the Netherlands. Provides volume controls, display brightness controls, display contrast controls, and three programmable emergency keys.

#### DS7447V2-SPA LCD Keypad

**DS7447V2-SPA**

For use in Spain. Provides volume controls, display brightness controls, display contrast controls, and three programmable emergency keys.

#### DS7447V2-SWE LCD Keypad

**DS7447V2-SWE**

For use in Sweden. Provides volume controls, display brightness controls, display contrast controls, and three programmable emergency keys.

**Americas:**  
Bosch Security Systems, Inc.  
130 Perinton Parkway  
Fairport, New York, 14450, USA  
Phone: +1 800 289 0096  
Fax: +1 585 223 9180  
security.sales@us.bosch.com  
www.boschsecurity.us

**Europe, Middle East, Africa:**  
Bosch Security Systems B.V.  
P.O. Box 80002  
5600 JB Eindhoven, The Netherlands  
Phone: +31 40 2577 284  
Fax: +31 40 2577 330  
emea.securitysystems@bosch.com  
www.boschsecurity.com

**Asia-Pacific:**  
Robert Bosch (SEA) Pte Ltd, Security Systems  
11 Bishan Street 21  
Singapore 573943  
Phone: +65 6258 5511  
Fax: +65 6571 2698  
apr.securitysystems@bosch.com  
www.boschsecurity.com

#### Represented by